

Plasticolor

Plastic Bumper Coating

PLASTICOLOR is a durable coloured coating that adheres direct to most plastics†. It is fast drying and easy to blend out for an excellent finish on all exterior and interior hard plastics.

- Excellent coverage with easy blend out
- Colour matched to current bumper shades
- Very fast drying
- Unique Vari-nozzle giving broad atomisation and high yield
- Excellent adhesion to most plastics

Suitable substrates

Suitably prepared Plastics - PP, PP/EPDM, ABS.

† For ultimate adhesion, always apply over ProXL PLASTIGRIP

Application data



3 - 4 coats



5 minutes @ 20°C



Dust free	8-15 minutes
Touch Dry	30-45 minutes
Hard Dry	60 minutes

Application method



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.

Jet Black	
Black 1	
Traffic Black	
Smoke Grey	
Mid Grey 3	
Mid Grey 2	
Dark Grey	
Mid Grey	
Light Grey	



Plasticolor

Plastic Bumper Coating

Technical data

Chemical base	Acrylic combination
VOC content	241.2 g/400ml
Coverage	0.8 - 1.0 m ²
Storage notes	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)

Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

