Revision: 14.04.2021



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PROXL GENERATION20 HIGH SOLIDS STONECHIP GREY (1LT)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 No further relevant information available.
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Capella Solutions Group

1 Mantle Close

Bingham Road, Sittingbourne, Kent, ME9 3BW

Tel: +44 (0)1634 823900

E-mail: sales@capellasolutionsgroup.com

- · Further information obtainable from: Product safety Department
- · 1.4 Emergency telephone number: Tel:

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS(

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light Naphtha (petroleum), hydrotreated light

Naphtha (petroleum), hydrotreated light

Solvent naphtha (petroleum), light arom.

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 2)

Revision: 16.03.2021



Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with additions.

· Dangerous components:		
CAS: 64742-49-0 EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; SAsp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-<25%
CAS: 64742-49-0 EC number: 920-750-0 Reg.nr.: 01-2119473851-33-0001	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	5-<10%
CAS: 64742-49-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Naphtha (petroleum), hydrotreated light The Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; SASP. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	5-<10%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Revision: 16.03.2021

generation Q

Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

(Contd. of page 2)

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	Long-term - systemic effects, general population	149 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	300 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	149 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	2,085 mg/m3 (Worker)
	Long-term - systemic effects, general population	477 mg/m3 (General Population)
CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	Long-term - systemic effects, general population	699 mg/kg bw/day (General Population)

Contd. on page 4

Revision: 16.03.2021



Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

		(Contd. of page 3)
Dermal	Long-term - systemic effects, worker	773 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	699 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	2,035 mg/m3 (Worker)
	Long-term - systemic effects, general population	608 mg/m3 (General Population)
CAS: 6474	2-49-0 Naphtha (petroleum), hydrotreated light	
Oral	Long-term - systemic effects, general population	699 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	773 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	699 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	2,035 mg/m3 (Worker)
	Long-term - systemic effects, general population	608 mg/m3 (General Population)
CAS: 6474	2-95-6 Solvent naphtha (petroleum), light arom.	
Oral	Long-term - systemic effects, general population	11 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	25 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	11 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	150 mg/m3 (Worker)
	Long-term - systemic effects, general population	32 mg/m3 (General Population)

[·] Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Filter A

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 16.03.2021

Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

generation:

· Eye protection:



Tightly sealed goggles

· **Body protection:** Use protective suit.

9.1 Information on basic physical and General Information Appearance: Form: Colour:	d chemical properties Fluid
Appearance: Form: Colour:	Fluid
Form: Colour:	Fluid
Colour:	1 titti
	Grev
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ran	ge: 94-99 °C
Flash point:	-7 °C (DIN 53213)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	7 Vol %
Vapour pressure At 20 °C:	60 hPa
Density At 20 °C:	1.08 g/cm³ (DIN 51757)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water	: Not determined.
Viscosity:	1.500 B
Dynamic At 20 °C:	1,500 mPas
Kinematic:	Not determined.
Solvent content:	46.004
Organic solvents:	46.0 %
Water:	0.1 %
Solids content:	53.8 % (DIN 53216)
9.2 Other information	No further relevant information available.
VOC (EU): VOC (EU):	46.05 % 497.3 g/l

(Contd. on page 6)

Revision: 16.03.2021

Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

(Contd. of page 5)

· VOCV: 46.05 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· LD/LC50 values relevant for classification:

· Acute toxicity Based on available data, the classification criteria are not met.

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	LD50	>5,840 mg/kg (RAT)
Dermal	LD50	>2,920 mg/kg (RAT)
Inhalative	LC50/4 h	>5,840 mg/kg (RAT) >2,920 mg/kg (RAT) >23.3 mg/l (RAT)
CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		

d light

Oral	LD50	>5,000 mg/kg (RAT)
Dermal	LD50	>2,800 mg/kg (RABBIT)
Inhalative	LC 50	> 23.3 mg/l (RAT)

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>5,840 mg/kg (RAT)
Dermal	LD50	>2,920 mg/kg (RABBIT)
Inhalative	LC50/4 h	>25.2 mg/l (RAT)

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	3,492 mg/kg (RAT)
Dermal		>3,160 mg/kg (RABBIT)
Inhalative	LC50/4 h	>6,193 mg/l (RAT)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- $\cdot \textit{Serious eye damage/irritation} \ \textit{Based on available data, the classification criteria are not met.}$
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

Revision: 16.03.2021

Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

generation.

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	xicity:	
CAS: 6474	2-49-0 Naphtha (petroleum), hydrotreated light	
LL50/96 h	>13.4 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS)	
EL50/48 h	3 mg/l (DAPHNIA MAGNA)	
EL50/72 h	10-30 mg/l (SELENASTRUM CAPRICORNUTUM)	
CAS: 6474	2-49-0 Naphtha (petroleum), hydrotreated light	
LL50/96 h	>13.4 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS)	
EL50/48 h	3 mg/l (DAPHNIA MAGNA)	
EL50/72 h	10-30 mg/l (SELENASTRUM CAPRICORNUTUM)	
CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		
LL50/96 h	11.4 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS)	
EC50/48 h	10 mg/l (PHAEOPHYTA)	
EL50/48 h	3 mg/l (DAPHNIA MAGNA)	
EL50/72 h	30-100 mg/l (SELENASTRUM CAPRICORNUTUM)	
CAS: 6474	2-95-6 Solvent naphtha (petroleum), light arom.	
LL50/96 h	9.2 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS)	
EC50/48 h	7.4 mg/l (DAPHNIA MAGNA)	
EL50/48 h	3.2 mg/l (DAPHNIA MAGNA)	
EL50/72 h	2.9 mg/l (SELENASTRUM CAPRICORNUTUM)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

	,,
· European waste catalogue	
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

(Contd. on page 8)

Revision: 16.03.2021

Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

(Contd. of page 7)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	n
14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1139
14.2 UN proper shipping name ADR/RID/ADN	1139 COATING SOLUTION, ENVIRONMENTALL HAZARDOUS, special provision 640D
IMDG	COATING SOLUTION (HEPTANES, Naphth (petroleum), hydrotreated light), MARINE POLLUTANT
IATA	COATING SOLUTION
14.3 Transport hazard class(es)	
ADR/RID/ADN, IMDG	
Class Label	3 Flammable liquids. 3
IATA	
Class Label	3 Flammable liquids.
14.4 Packing group ADR/RID/ADN, IMDG, IATA	II
14.5 Environmental hazards:	Product contains environmentally hazardous substances Naphtha (petroleum), hydrotreated light
Marine pollutant:	Yes
Special marking (ADR/RID/ADN):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Transport in bulk according to Annex Marpol and the IBC Code	II of Not applicable.
Transport/Additional information:	Tansport classification ADR/IMGD is based on packagin > 30ltr(IMDG), < 450ltr(ADR).
	For other packaging untis different classification ca apply.
ADR/RID/ADN	
емсерией quantutes (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
ADR/RID/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 n

Revision: 16.03.2021

Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

	(Contd. of page 8
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1139 COATING SOLUTION, SPECIAL PROVISION 640D, 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS0

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

Naphtha (petroleum), hydrotreated light

Naphtha (petroleum), hydrotreated light

Solvent naphtha (petroleum), light arom.

- · Hazard statements
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- *H411 Toxic to aquatic life with long lasting effects.*
- · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

Revision: 16.03.2021



Trade name: HSG20SCG-1 - HIGH SOLIDS STONECHIP GREY (1LT)

(Contd. of page 9)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
Wasser	0.1
NK	46.0

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department.

Allaniations and announced

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB