

PROPELLING EXCELLENCE
PROXL[®]

generation™
20



AUTOMOTIVE ADHESIVES / SEALANTS / FOAMS

FOAMS

The 2k Urethane foams are available in both rigid and semi-rigid finishes. Applications include promoting sound deadening and reinforcement of hollow sections found in the automotive industry.



SEALERS

2k PU sealers are one of the most largely used products in the collision repair market. They keep out moisture and perfectly replicate the sprayed or brushed effect around door seals.

ADHESIVES

ProXL Bonding products have been developed to bond plastic and metal parts found in the automotive collision industry. The range includes a 35 second, 1 and 5 minute working time for bonding both plastic and metal parts.

SEALERS

ULTRASEAL

CODE	DESCRIPTION	SIZE	COLOUR	WORKING TIME*	PAINTING TIME	PRODUCT DETAILS
PROSEAL-SL	Self Levelling Seam Sealer	50ml	Grey	15 mins	30 mins	A 2k Urethane self-leveling seam sealer especially designed for structural bonding of a wide range of applications such as truck seams, drip rails, roof seams and core support.
PROSEAL-SL200		200ml				
PROSEAL-MB	Medium Build Seam Sealer	50ml	Grey	15 mins	30 mins	A medium build 2k Urethane non-sag seam sealer duplicates a factory appearance on truck bed seams, tooled door skin seams, floor pan seams, core support seams. To be used to re-create the sprayed effect.
PROSEAL-MB200		200ml				
PROSEAL-HB	High Build Seam Sealer	50ml	Grey	15 mins	30 mins	A high build 2k for use in vertical or horizontal seams to match OEM sealers applied in rectangular shaped bead. The product is non-sagging and no-flowing, used to re-create the sprayed and brushed effect.
PROSEAL-HB200		200ml				
SEALPU-RB	Rapid PU Sealer	310ml	Black	40 mins	Wet-on-wet	A rapid PU sealer that provides strong adhesion and fast curing times. Outstanding adhesion to sheet iron, aluminium, stainless steel, lead, copper, ceramic, glass, wood and various plastics. Excellent flexibility with no shrinkage or sticky surface.
SEALPU-RG			Grey			
SEALPU-RW			White			
PROSEAL-MSS	Sprayable Seam Sealer	310ml	Black	20-30 mins	Wet-on-wet	This high solids moisture-curing MS Polymer seam sealer provides a fast method of sealing trunk and floor pan seams, quarter panel seams, and any other seam where a sprayed or coated appearance is necessary. It can be caulked or sprayed as a sealer or a sound deadening coating.
PROSEAL-BR	Brushing Seam Sealer	1Litre	Grey	30 mins	n/a	A 1K Polymer based brushable, overpaintable seam sealer producing a durable sealant for joints and seams that have been bolted, riveted or spot welded.



CODE	DESCRIPTION	SIZE	COLOUR	WORKING TIME*	SANDING TIME*	PAINTING TIME	PRODUCT DETAILS
PROPLAS-R	Plastic Adhesive Ultra Fast	50ml	Black	35 sec	15 mins	40 mins	A rapid curing 2k Urethane adhesive with a ultra fast gel and curing time. Can be used for general purpose glueing or to hold part in position.
PROPLAS-F	Plastic Adhesive Fast	50ml	Black	1 min	20 mins	1 hour	A 2k Urethane fast plastic repair structural adhesive to repair any kind of plastic part. One minute working time makes this product suitable for small size repairs.
PROPLAS-FC			Clear				
PROPLAS-S	Plastic Adhesive Slow	50ml	Black	5 mins	30 mins	90 mins	A 2k Urethane plastic repair structural adhesive to repair any kind of plastic part. Five minutes working time makes this product suitable for large size repairs.
PROMET	Metal Adhesive	50ml	Black	20 mins	8 hours	12 hours	A 2k Urethane used to bond steel and aluminum. The primary use is to replace quarter panels, roofs, box sides, van sides, utility vehicle sides and door skins.
PROMET-200		200ml					
PROSCREEN	Rapid Windscreen Adhesive	310ml	Black	15 mins	n/a	n/a	An isocyanate-free, high modulus Polymer windscreen adhesive with rapid drying times that allow quick drive-away times as well as easy application.
PROBOND-B	Rapid Panel Adhesive	310ml	Black	15 mins	n/a	n/a	A high quality 1K Polymer-based adhesive with high strength and outstanding initial tack. It is suitable for bonding heavy materials without the use of clamps and/or fixing tape.



* Working time and sanding time are referred to a room temperature of 20°C, performances may change due to temperature variation

CODE	DESCRIPTION	SIZE	COLOUR	WORKING TIME*	PAINTING TIME	PRODUCT DETAILS
PROFOAM-G	Semi-Rigid Foam	50ml	Grey	1 min	1 hour	A 2k semi rigid Urethane which foams in place to fill posts, pillars, and automotive body cavities. Grey in colour with a soft density.
PROFOAM-G200		200ml				
PROFOAM-W	Rigid Foam	50ml	White	1 min	1 hour	A 2k rigid Urethane which foams in place to fill posts, pillars, and automotive body cavities. White in colour with a hard density.
PROFOAM-W200		200ml				



PROPELLING EXCELLENCE
PROXL

generation™
20



proxl.com

Follow us online



Product code: G20BONDLEAF

