Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

## SECTION 1: Identification of the substance/mixture and of the company/ Undertaking

#### 1.1 Product identifier

Product name ProSeal 2K PU Self Levelling Seam Sealer – Ochre Grey -Part A

**1.2 Relevant identified uses of the substance or mixture and uses advised against** Intended use Polyurethane based adhesive

### 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Capella Solutions Group 1 Mantle Close Off Bingham Road, Sittingbourne ME10 3BW Kent United Kingdom Further information obtainable from: <u>sales@capellasolutionsgroup.com</u>

#### 1.4 Emergency telephone number:

+44 (0)203 394 9871 (24 hours, UK number, English) For technical and commercial enquiries call +44 (0)1634 823900

## SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication: Eye irritation, category 2

H319

Causes serious eye irritation.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Safety data sheet

Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

Hazard statements:
--------------------

H319Causes serious eye irritation.Precautionary statements:P280P337+P313If eye irritation persists: Get medical advice / attention.

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/info	rmation on ingre	dients
3.1. Substances.		
Contains:		
<b>Identification</b> Ethylenedinitrilotetrapropan-2-ol	x = Conc. %	Classification 1272/2008 (CLP) 1,1',1",1"'-
CAS 102-60-3	10 ≤ x < 20	Eye Irrit. 2 H319
EC 203-041-4		
INDEX -		
Reg. no. 01-2119552434-41-0001		
Glicerilpoli(ossipropilen)triammina		
CAS 64852-22-8	1 ≤ x < 3	Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic
EC INDEX –		3 H412

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.


SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.



Revision nr. 1

Dated 14.08.2023

## 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures.

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.



Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

#### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection.

#### 8.1. Control parameters.

#### 1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol

Predicted no-effect concentration - Predicted no-effect concentratio - Predicted no-effect concentrati	NEC
--	-----

Normal value in fresh water	0,085	mg/l
Normal value in marine water	0,0085	mg/l
Normal value for fresh water sediment	0,193	mg/kg
Normal value for marine water sediment	0,0193	mg/kg
Normal value for water, intermittent release	1,51	mg/l
Normal value of STP microorganisms	70	mg/l
Normal value for the terrestrial compartment	0,0183	mg/kg

#### Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers.				Effects on workers			
Route of	Acute local	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
exposure		systemic	local	systemic		systemic	local	systemic
Oral.			VND	2,5 mg/kg/d				
Inhalation.			VND	8,7 mg/m3			VND	29,4 mg/m3
Skin.			VND	2,5 mg/kg/d			VND	4,2 mg/kg/d

Legend:

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

Printing date 14.08.2023

Revision nr. 1



Dated 14.08.2023

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	grey
Odour	no odour
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	> 200 °C
Boiling range	Not available
Flash point	182 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Vapour pressure	0,1 Pa
Vapour density	Not available
Relative density	1,01 g/cm3
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

### 9.2. Other information

Total solids (250°C / 482°F) 9,95 % VOC (Directive 2010/75/EC) : 0 VOC (volatile carbon) : 0

## SECTION 10. Stability and reactivity.

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

Safety data sheet

*Printing date 14.08.2023* 

Revision nr. 1

Dated 14.08.2023

1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol

Materie da evitare : acidi forti, ossidanti forti, prodotti chimici reattivi, basi forti

### 10.6. Hazardous decomposition products.

Information not available.

## SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information Information not available

Information on likely routes of exposure Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure Information not available

Interactive effects Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: Not classified (no significant component) LD50 (Dermal) of the mixture: Not classified (no significant component)

Glicerilpoli(ossipropilen)triammina LD50 (Oral) 2690 mg/kg LD50 (Dermal) 12500 mg/kg

SKIN CORROSION / IRRITATION Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION Does not meet the classification criteria for this hazard class

Safety data sheet

Printing date 14.08.2023

Revision nr. 1

PROPELLING EXCELLENCE

Dated 14.08.2023

GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class

CARCINOGENICITY Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD Does not meet the classification criteria for this hazard class

## SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

### 12.1. Toxicity

Glicerilpoli(ossipropilen)triammina LC50 - for Fish 68 mg/l/96h

### 12.2. Persistence and degradability

Information not available

### 12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects

Information not available

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

## Safety data sheet



Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## SECTION 15. Regulatory information.

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product. Point

Substances in Candidate List (Art. 59 REACH)

З

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Safety data sheet



Printing date 14.08.2023

Revision nr. 1

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:


Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

- CAS NUMBER: Chemical Abstract Service Number

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%



Revision nr. 1

Dated 14.08.2023

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

09.

Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

## SECTION 1: Identification of the substance/mixture and of the company/ Undertaking

#### 1.1 Product identifier

Product name ProSeal 2K PU Self Levelling Seam Sealer - Ochre Grey - Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against Intended use Polyurethane based adhesive

#### 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Capella Solutions Group 1 Mantle Close Off Bingham Road, Sittingbourne ME10 3BW Kent United Kingdom Further information obtainable from: sales@capellasolutionsgroup.com

#### 1.4 Emergency telephone number:

+44 (0)203 394 9871 (24 hours, UK number, English) For technical and commercial enquiries call +44 (0)1634 823900

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	<i>Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation.</i>
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Respiratory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.

### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

## Safety data sheet



Printing date 14.08.2023

Revision nr. 1

Signal words:

14.

Hazard statements:

H351	Suspected of causing cancer.	
110-0	• • • • •	

Danger

- H373 May cause damage to organs through prolonged or repeated exposure.
- H319 Causes serious eye irritation.

H315 Causes skin irritation.

- H335 May cause respiratory irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- EUH204 Contains isocyanates. May produce an allergic reaction.

### Precautionary statements:

P201	Obtain special instructions before use.
P284	[In case of inadequate ventilation] wear respiratory protection.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Contains: 4,4'-Methylenediphenyl diisocyanate, oligomers

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/inf	ormation on ingredients	
3.1. Substances.		
Information not relevant.		
3.2. Mixtures.		
Contains:		
Identification.	Conc. %.	Classification 1272/2008 (CLP).
4,4'-Methylenediphenyl diisocyanate	, oligomers	
CAS. 26447-40-5	50 - 55	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1A H317
EC. 247-714-0		
INDEX. 615-005-00-9		

Printing date 14.08.2023

Revision nr. 1



Dated 14.08.2023

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures.

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

#### 5.3. Advice for firefighters.

GENERAL INFORMATION

Safety data sheet



*Printing date 14.08.2023* 

Revision nr. 1

Dated 14.08.2023

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

### 7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

Printing date 14.08.2023

Revision nr. 1



Dated 14.08.2023

SECTION 8. Exposure controls/personal protection.						
8.1. Control parameters.						
Regulatory References:						
TLV-ACGIH ACGIH 2014						
4,4'-Methylenediphenyl diisocyanate, oligomers						
Threshold Limit Value.						
Туре	Country	TWA/8h		STEL/15mi	n	
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGII	Н		0,005			
Predicted no-effect concentration - PNEC.						
Normal value in fresh water				1		mg/l
Normal value in marine water				0,1		mg/l
Normal val	lue of STP microor	ganisms		1		mg/l
Normal val	lue for the terrestria	al compartment	1		mg/kg	

#### Health - Derived no-effect level - DNEL / DMEL

	Effects on consumers.				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	20 mg/kg bw/d						
Inhalation.	0,05 mg/m3	VND	0,025 mg/m3	0,025 mg/m3	0,1 mg/m3	0,1 mg/m3	0,05 mg/m3	0,05 mg/m3
Skin.	17,2 mg/cm2	25 mg/kg bw/d			28,7 mg/cm2	50 mg/kg bw/d		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

## HAND PROTECTION

Safety data sheet



Printing date 14.08.2023

Revision nr. 1

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

#### 9.1. Information on basic physical and chemical properties.

Appearance Colour Odour Odour threshold. pH. Melting point / freezing point. Initial boiling point. Boiling range. Flash point. Evaporation Rate Flammability of solids and gases Lower inflammability limit.	liquid yellowish Not available. Not available. Not available. > 300 °C. Not available. 205 °C. Not available. Not available. Not available.
Flammability of solids and gases	
Lower inflammability limit. Upper inflammability limit. Lower explosive limit. Upper explosive limit.	Not available. Not available. Not available. Not available.

## Safety data sheet



Printing date 14.08.2023

Vapour pressure.

Vapour density

Solubility

Viscosity

Relative density.

Partition coefficient:

Auto-ignition temperature.

Decomposition temperature.

Revision nr. 1

Dated 14.08.2023

0,01 Pa Not available. 1,100 Kg/l insoluble in water n-octanol/water Not available. > 600 °C. Not available. 2000 mPas Not available. Not available.

### 9.2. Other information.

Explosive properties

Oxidising properties

VOC (Directive 2010/75/EC) : 0 VOC (volatile carbon) : 0

## SECTION 10. Stability and reactivity.

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials.

Information not available.

#### 10.6. Hazardous decomposition products.

Information not available.

## SECTION 11. Toxicological information.

#### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible carcinogenic effects. Anyway, currently available data do not allow us to comprehensively assess this product.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Safety data sheet



Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Acute effects: inhalation of this product may irritate the lower and upper respiratory tract and cause cough and respiratory disorders; at higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

This product contains isocyanates. Producer's specifications are as follows: Ready-to-use products containing isocyanates may irritate mucosas, particularly those of the respiratory system, and may give rise to hypersensitivity reactions. Vapour or aerosol inhalation may lead to sensitization. Please take all the measures used for all solvent-containing products while manipulating isocyanate-containing products. Avoid vapour and aerosol inhalation. People with allergic or asthmatic precedents or subject to respiratory disorders should not handle products containing isocyanates.

4,4'-Methylenediphenyl diisocyanate, oligomers LD50 (Oral).> 5000 mg/kg

LD50 (Dermal).> 9400 mg/kg

LC50 (Inhalation).0,49 mg/l/4h

## SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.



Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

## 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# SECTION 14. Transport information.

### 14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

### 14.4. Packing group.

Not applicable.

### 14.5. Environmental hazards.

Not applicable.

### 14.6. Special precautions for user.

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

Safety data sheet



Printing date 14.08.2023

Revision nr. 1

ISECTION	115 Reau	latory	information.
	10.11090	i alory	

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.					
Seveso category.	None.				
Restrictions relating to a	the product or co	ontained substances pursuant to Annex XVII to EC Regulation 1907/2006.			
Product. Point.	3				
Contained substance. Point.	56	4,4'-Methylenediphenyl diisocyanate, oligomers			
Substances in Candidate List (Art. 59 REACH). None.					
Substances subject to authorisarion (Annex XIV REACH). None.					
Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None.					
Substances subject to the Rotterdam Convention: None. Substances subject to the Stockholm Convention: None.					
Healthcare controls. Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.					

## 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.

PROSEAL-SL; PROSEAL-SL200 Safety data sheet



Printing date 14.08.202		Revision nr. 1	Dated 14.08.2023
H334		sthma symptoms or breathing difficultie	
H317	May cause an allergic		
EUH204	,	May produce an allergic reaction.	
LEGEND:			
- ADR: European Agree	ment concerning the ca	rriage of Dangerous goods by Road	
- CAS NUMBER: Chem	nical Abstract Service Nu	ımber	
- CE50: Effective conce	entration (required to ind	uce a 50% effect)	
- CE NUMBER: Identifie	er in ESIS (European ar	chive of existing substances)	
- CLP: EC Regulation 1			
- DNEL: Derived No Eff			
- EmS: Emergency Sch			
-	-	cation and labeling of chemicals	
	•	tion Dangerous Goods Regulation	
- IC50: Immobilization (			
	laritime Code for danger	ous goods	
- IMO: International Ma	-	8	
	ntifier in Annex VI of CLI	5	
- LC50: Lethal Concent - LD50: Lethal dose 50			
- OEL: Occupational Ex			
	cumulative and toxic as	REACH Regulation	
- PEC: Predicted enviro		IEACH Regulation	
- PEL: Predicted expos			
- PNEC: Predicted no e			
- REACH: EC Regulation			
-		ransport of dangerous goods by train	
- TLV: Threshold Limit \	-		
- TLV CEILING: Concer	ntration that should not b	be exceeded during any time of occupa	itional exposure.
- TWA STEL: Short-terr	n exposure limit		
- TWA: Time-weighted a	- ·		
- VOC: Volatile organic	•		
-	•	ive as for REACH Regulation	
- WGK: Water hazard c	, ,		
GENERAL BIBLIOGRA		Furner and Deutline and	
- , ,	7/2006 (REACH) of the	•	
	2/2008 (CLP) of the Eur /2009 (I Atp. CLP) of the	•	
• • • •	5/830 of the European F	•	
- , ,	/2011 (II Atp. CLP) of the		
- , ,	/2012 (III Atp. CLP) of th	-	
- , ,	/2013 (IV Atp. CLP) of th	-	
- , ,	/2013 (V Atp. CLP) of the	•	
- , ,	/2014 (VI Atp. CLP) of th	-	
- The Merck Index 10	,		
- Handling Chemical Sa	afety		
- INRS - Fiche Toxicolo	gique (toxicological shee	∍t)	
- Patty - Industrial Hygie	ene and Toxicology		
- N.I. Sax - Dangerous	properties of Industrial N	Naterials-7, 1989 Edition	
- ECHA website			
Note for users:			
	-	are based on our own knowledge on th	
must verity the suitabilit	ly and thoroughness of p	provided information according to each	specific use of the product.

# Safety data sheet



Printing date 14.08.2023

Revision nr. 1

Dated 14.08.2023

This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.